

REC'D PCT/PTC 07 OCT 2004

P1 1039999

REC'D 22 JUL 2003

WIPO PCT

# THE UNITED STATES OF AMERICA

**TO ALL TO WHOM THESE PRESENTS SHALL COME:**

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office

July 16, 2003

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM  
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK  
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT  
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A  
FILING DATE.

APPLICATION NUMBER: 60/371,773

FILING DATE: April 10, 2002

RELATED PCT APPLICATION NUMBER: PCT/US03/11010

By Authority of the  
COMMISSIONER OF PATENTS AND TRADEMARKS



*E. Bornett*  
E. BORNETT  
Certifying Officer

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

04-12-02

A/P

04/10/02  
3C769 U.S. PTO


Please type a plus sign (+) inside this box 

PTO/SB/16 (8-00)  
Approved for use through 10/31/2002 OMB 0651-0032  
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

3C769 U.S. PTO  
04/10/02

INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
Manoranjan Peter		Misra Lenz		Reno, Nevada, USA Reno, Nevada, USA	
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
Hydroxide-gel Coagulation and Pre-coat Filtration Of Arsenic from Drinking and Process Water					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input checked="" type="checkbox"/> Customer Number		23713		 Place Customer Number Bar Code Label here PATENT TRADEMARK OFFICE	
OR Type Customer Number here					
<input checked="" type="checkbox"/> Firm or Individual Name		Greenlee Winner & Sullivan, P.C.			
Address		5370 Manhattan Circle			
Address		Suite 201			
City		Boulder	State	CO	ZIP 80303
Country		USA	Telephone	303-499-8080	Fax 303-499-8089
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		27		<input type="checkbox"/> CD(s), Number	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets		2		<input checked="" type="checkbox"/> Other (specify)	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76		Certificate of Mailing			
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
<input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fees				FILING FEE AMOUNT (\$)	
<input type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number				\$160.00	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME

TELEPHONE

Susan K. Doughty

303-499-8080

Date

4/10/02

REGISTRATION NO.

(if appropriate)

Docket Number:

43,595

40-02P

## USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C.

P19LARGE/REV05

# PROVISIONAL APPLICATION FOR LETTERS PATENT

Inventors: Manoranjan Misra  
Peter Lenz

## HYDROXIDE-GEL COAGULATION AND PRE-COAT FILTRATION OF ARSENIC FROM DRINKING AND PROCESS WATER

Prepared by:

Greenlee, Winner and Sullivan, P.C.  
5370 Manhattan Circle, Suite 201  
Boulder, Colorado 80303  
(303)499-8080


Attorney Docket Number: 40-02P  
11a:4/10/02

### CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited  
with the United States Postal Service with sufficient postage  
for Express Mail in an envelope addressed to:

The Assistant  
Commissioner for Patents,  
Washington, D.C., 20231

April 10, 2002  
Date

  
Loretta Allenenos

EL 936708745 US  
Express Mail No.

## HYDROXIDE-GEL COAGULATION AND PRE-COAT FILTRATION OF ARSENIC FROM DRINKING AND PROCESS WATER

### BACKGROUND OF THE INVENTION

Arsenic is a naturally occurring element in the earth's crust and can be found in many natural ecosystems. Mining of ores containing arsenic releases it into the soil. Burning of arsenic containing fossil fuels, volcanic eruptions and weathering processes also introduce substantial amounts of arsenic into the environment. Various industrial activities such as smelting, petroleum refining, pesticide and herbicide manufacturing, glass and ceramic production generate arsenic containing wastewater. Its presence in natural waters may originate from geochemical reactions, industrial waste discharges or agricultural use of pesticides containing arsenic (Gupta and Chen, 1978). Most of the gold and silver ores are closely associated with arsenic compounds. Arsenic is present in the gold cyanidation process. It is present in gold extraction processes, which utilize roasting, pressure autoclaving and other oxidation pathways.

The major issue in studies related to arsenic in the environment has involved its deleterious effects on the environment. Arsenic is mobile within the environment and may circulate many times in various forms through the atmosphere, water and soil before finally entering to sediments (Ahmann et al., 1997).

Hyperpigmentation, skin cancer, liver cancer, circulatory disorders, and other ailments have been attributed to the presence of arsenic in water (National Academy of Sciences, 1977; National Research Council, 1999). The United States Environmental Protection Agency (USEPA) has identified arsenic as a group A "known" carcinogen. This classification is based on sufficient evidence of carcinogenicity from human data involving occupational and drinking water exposures. Arsenic presents a potential health problem due to its toxicity. In response to these health concerns, the USEPA, in January 2001, promulgated the new Arsenic rule that

lowered the maximum contaminant level (MCL) in drinking water to 10  $\mu\text{g/L}$  (10 ppb) for both community and non-transient, non-community water systems. Previously, the Safe Drinking Water Act (SDWA) had a minimum standard of 50 ppb. EPA lowered the standard based on recommendations by the National Research Council (1999) who reviewed scientific studies on health effects of arsenic on human populations. At present, approximately 4000 drinking water systems in the U.S. will need to comply with the new standard by January 2006, and many of these systems are located in rural areas of the West. Conventional water treatment systems will cost the nation between \$180 and \$725 million to meet the 10 ppb standard set by EPA.

### Chemistry of Arsenic

Arsenic occurs in inorganic form in aquatic environments, resulting from the dissolution of solid phases such as arsenolite ( $\text{As}_2\text{O}_3$ ), arsenic anhydride ( $\text{As}_2\text{O}_5$ ) and realgar ( $\text{AsS}_2$ ). The chemistry of arsenic in aquatic systems is complex because the element can be stable in four major oxidation states (+5, +3, 0 and -3) under different redox conditions. In natural waters arsenic is found as an anion with acid characteristics in only the As(III) and As(V) oxidation states. In oxygenated waters, the oxyanions of arsenic exist in four different arsenate species as  $\text{H}_3\text{AsO}_4$ ,  $\text{H}_2\text{AsO}_4^-$ ,  $\text{HAsO}_4^{2-}$  and  $\text{AsO}_4^{3-}$  in the pH ranges of <2, 3-6, 8-10 and >12, respectively. Arsenite is more likely to be found in oxygen free (anaerobic) groundwater, while arsenate is more common in aerobic surface water. Arsenite ion is oxidized to arsenate in the presence of oxygen chlorine or potassium permanganate. Therefore under neutral conditions and acidic conditions, As(III) exists as a neutral species and cannot be adsorbed by an adsorbent based on ionic interaction alone. The chemistry of arsenic is more fully described in U.S. Patent 6,197,201.

Several methods for reducing arsenic concentrations to acceptable levels have been studied and are being used currently. These methods include coagulation and precipitation using ferric chloride and sulfate, ion exchange, reverse osmosis and adsorption using activated carbon and alumina. These methods are effective to a certain extent. However, these methods are considerably more expensive and generally narrower in application than is desired for the treatment of large volumes of water.

The use of ferric chloride, hydrated lime, sodium sulfate and alum to coagulate water containing arsenic has been described (Harper and Kingham, 1992). These methods require multiple treatments of water with coagulation chemicals and large amounts of chemicals relative to the amount of arsenic present to obtain the desired reduction in arsenic concentration. In addition, the methods produce sludge that requires dewatering or solidification and eventually landfill storage as hazardous waste. Also, the ferric chloride process requires pH of less than 6.5 (Merrill et al., 1987).

A method of precipitating arsenite and arsenate ions from aqueous solutions using yttrium carbonate at alkaline pH has also been described (Wasay et al., 1996). This method requires strict control of pH to achieve removal sufficient to comply with environmental standards. In addition, the effective pH range was found to depend on which arsenic species was desired to be precipitated.

United States Patent 3,956,118 discloses a process for removing phosphate ions from waste waters using a rare earth salt. However, the disclosed process is limited to removal of phosphates.

Recently new adsorbents, lanthanum oxide and lanthanum-alumina oxide, have been used for removing arsenate and arsenite species from solution (U.S. Patent No. 5,603,838, 1995). This patent discloses that lanthanum oxide alone or in conjunction with alumina solids and other oxides can remove arsenic to low levels (<50 ppb). Also, the adsorption kinetics were found to be extremely fast compared to other adsorbents such as alumina (Davis and Misra, 1997; Misra and Adutwum, 2000; Misra et al., 1997; Rawat and Misra, 1998).

A novel precipitation process developed by Misra et al. (U.S. Patent No. 6,197,201) uses lanthanum chloride and optionally other salts to selectively coprecipitate arsenite and arsenate from process water (Misra et al., 2000; Nanor, Misra, and Chen, 1999; Nanor and Misra, 1998).

General drawbacks of the processes discussed above include inefficient removal of arsenic to an acceptably low level for drinking water and discharge into ground water, the

problem of filtration of precipitated sludge and fouling of resins and membranes. In addition, once the arsenic species are removed, the solid materials formed must be disposed of. The solid materials formed from the processes above are also susceptible to leaching of the metals at a future time.

There is a need to find a highly selective and inexpensive reagent, which effectively precipitates and stabilizes arsenate and arsenite species over a wide pH range, from solutions or solids/liquid mixtures. There is also a need to find an inexpensive, suitable media for the filtration of adsorbed arsenic species.

#### BRIEF SUMMARY OF THE INVENTION

This invention is in the field of removal of toxic metals from aqueous solutions and stabilizing toxic metals, specifically removal of arsenic from aqueous solutions and drinking water.

It was found that lanthanum hydroxide is a powerful reagent to precipitate arsenic as arsenite and arsenate ions, for example from aqueous solution at various pHs. The lanthanum hydroxide used can be pure or can be mixed with other elements of the lanthanide series. Lanthanum hydroxide can also be used in combination with other metals such as ferric hydroxide, magnesium hydroxide, sodium hydroxide and/or aluminum hydroxide. A preferred embodiment is the combination of iron chloride and lanthanum chloride at various ratios which form mixed metal salt hydroxide gels which are used to remove arsenic from solutions, as described herein. When a small amount of lanthanum chloride is added to solutions containing arsenite and arsenate in the presence of ferric ions, the ions substantially precipitate from the solution. The resultant precipitant is extremely stable and easy to filter. The precipitant may be filtered through a bed of diatomaceous earth (DE filter bed or DE bed), for example. Alternatively, a pre-coat DE bed may be used, where the DE is coated on a filter screen and the arsenic-containing solution is passed through the pre-coat DE bed. The filter screen may be polyethylene, for example, or other suitable material as known to one of ordinary skill in the art. DE coated with hydroxide-gels can be used to coagulate arsenic which can further be filtered through a second DE bed or pre-coat DE bed, if necessary to reduce the concentration of arsenic

to a desired level. Generally, the DE filter bed is made by filtering water conditioned with DE through a screen. The thickness of the DE bed ranges from ½ inch to several inches thick, as known by one of ordinary skill in the art.

Specifically, provided is a method of removing arsenic from arsenic-containing water comprising: contacting said water with a composition comprising a metal salt hydroxide-gel; and passing said composition through a filter, whereby arsenic-removed water is formed. The filter is preferably a DE filter bed or a pre-coat DE filter bed.

Also provided is a method of removing arsenic from arsenic-containing water comprising: coating DE with one or more metal salt hydroxide-gels to form DE pre-coated hydroxide-gels; and contacting said arsenic-containing water with said DE pre-coated hydroxide-gels.

In preferred methods of the invention, the metal salt hydroxide-gel is precipitated from one or more members of the group consisting of: lanthanum chloride, lanthanum nitrate, lanthanum carbonate, other rare earth salts, ferric chloride, ferric sulfate, magnesium chloride, magnesium nitrate, magnesium carbonate, aluminum chloride, aluminum nitrate, aluminum sulfate, and sodium aluminate. Other salts may be used, as known in the art. Hydroxide salts, such as  $\text{La}(\text{OH})_3$  may also be used differently to form the metal salt hydroxide-gel, without precipitating from another metal salt.

The methods of the invention are carried out at a pH which is sufficient to allow the desired reactions to occur, preferably between about 2 to about 14, more preferably between about 4 to about 10. The metal salt hydroxide-gel is contacted with the arsenic-containing water for a suitable time to allow the desired level of arsenic reduction to occur, typically between about 1 minute to about 30 minutes. The methods of the invention remove arsenic from arsenic-containing water having a variety of concentrations of arsenic, preferably about 10 ppb to several ppm. The arsenic-containing water may contain one or more species of arsenic, such as arsenite and arsenate. The methods of the invention may be used to treat any water, including raw water, well water, drinking water (chlorinated or not), and process water.



Preferably, the metal salt hydroxide-gel comprises lanthanum and iron, preferably at weight ratios of between about 1:1 and 1:10.

In the methods of the invention, the filter is preferably selected from the group consisting of: diatameous earth (DE), cellulose, and perlite, but any suitable material may be used, as known in the art. The arsenic-containing water is contacted with the metal salt hydroxide-gel by any means known in the art, including mechanical mixing, ultrasonic mixing, mixing in-line using an atomizer, mixing in-line using venturi and using metering pumps. The methods of the invention may further comprise separating the arsenic-removed water from the arsenic-containing hydroxide-gels. This separating may be accomplished by any means known in the art, including settling, DE-assisted settling, flotation of hydroxide-gels or DE-assisted centrifuge. The arsenic-containing sludge, consisting of hydroxide-gel and DE, is stable. Arsenic containing sludge passes the Toxicity Characteristics Leaching Procedure (TCLP) test.

DE filter aids are generally used in two different modes: as a precoat, wherein the DE acts as the solid/liquid separation surface barrier (albeit with some depth), and as body feed, wherein the DE acts to maintain a permeable cake structure and create a de-facto depth filtration. These two modes are used both in combination and individually, depending on the type and degree of difficulty of the filtration.

For precoat applications, the DE must be able to form a barrier tight enough to provide the desired clarity of filtrate, while at the same time be as open as possible to provide maximum filtrate throughput. When used as a body feed or ad-mix, the filter aid must be just tight enough to prevent migration of trapped solids through the forming cake.

The DE precoat is formed by passing a dilute suspension (generally less than 5% by weight) of DE in process water over a septum or screen. The septum serves as a support structure for the formation of the DE precoat. As the slurry passes through the septum, the DE solids are trapped on its surface and a precoat is formed. The precoat thickness can be as little as 1.5 mm and still provide adequate solid / liquid separation during subsequent filtration. The driving force during formation of the precoat can be either negative (vacuum) or positive pressure. The openings in the septum should be just small enough to trap the DE particles, but

can be highly variable in size and geometry. The septum can be constructed of any materials compatible with water, including stainless steel and polyethylene.

## DETAILED DESCRIPTION OF THE INVENTION

As used herein, "removing" means the concentration is reduced to a desired level. For example, "removing arsenic from arsenic-containing water" means reducing the concentration of arsenic, preferably in the form of arsenite and arsenate, in arsenic-containing water to a desired level, preferably to a concentration below 10 ppb. "Arsenic-containing water" may contain other elements other than arsenic. "Aqueous solution" refers to a solution in which water is the dissolving medium or solvent. A "precipitating composition" refers to any of the agents described herein that cause precipitation or stabilization of the ions of interest. A "solid" material refers to the resultant material formed from the contacting of the precipitating composition with the aqueous solution. Solid materials formed include amorphous materials and crystalline materials or mixtures. The pH of the aqueous solution is adjusted by any means known by one skilled in the art, including addition of calcium, hydroxide and sodium hydroxide to raise the pH or acid to lower the pH. A "concentration effective for removing at least one ion" refers to the concentration of precipitating composition required to remove a measurable amount of the selected ion. "Lanthanum chloride" refers to both pure and impure lanthanum chloride. Impure lanthanum chloride can contain various elements of the lanthanide series in addition to lanthanum. The lanthanide series of elements includes the elements lanthanum, cerium, praseodymium, neodymium, etc. Ferric hydroxides can be prepared from ferric chloride, ferric sulfate, and ferric nitrate, as known in the art. Other metal hydroxides can be prepared from other metal salts by mixing with lime, caustic, and magnesium oxide, as known in the art. As used herein, "contacting" means the arsenic-containing water and the metal salt hydroxide-gel are placed together so that the desired reaction occurs to the desired extent. As used herein, a "metal salt hydroxide-gel" is a hydroxide formed from a metal salt, which can be used in the methods of the invention to remove arsenic from arsenic-containing water. "Metal salt hydroxide gels" are hydroxides of metals formed from metal salts other than hydroxides

The processes of this invention achieve the removal of more than 99% of arsenic species in an aqueous solution. Concentrations of less than 5 parts per billion arsenic are achievable.

Solutions containing arsenic ions are contacted with a precipitating composition. For the removal or stabilization of arsenic ions, such compositions comprise from about 10-5000 moles of lanthanum for every mole of arsenic ions in solution. The compositions can comprise ferric ions in concentrations from about 1 mole to about 500 moles ferric ions for every mole of arsenic ion. The compositions can also optionally contain various elements of the lanthanide series and other metals.

The solution should remain in contact with the precipitating composition for a period of time sufficient to cause removal of arsenic ions to the desired concentration ranges. Typically about 5-30 minutes is sufficient to cause precipitation to the desired concentration range and/or stabilization of the arsenic when the concentration of arsenic in solution is between 12-100,000 ppb.

The process of this invention can be used to remove arsenic from solutions that contain one or more species of arsenic.

A preferred process of this invention involves adjusting the pH of the solution to between 6 and about 10, adding 1000 moles of lanthanum for every mole of arsenic ions present in solution, and adding about 5 to about 6 moles of ferric ions for every mole of arsenic ions present in solution. The chlorides form metal salt hydroxide-gels which stabilize the arsenic.

The invention is further illustrated by the following non-limiting examples.

In the examples below, bulk synthetic solutions were prepared for arsenic. All bulk solutions were made using deionized water. The lanthanum chloride used can be pure lanthanum chloride or lanthanum carbonate treated with hydrochloric acid. Ferric chloride can be obtained from a variety of commercial sources. The schematic of a preferred embodiment is given in Figure 1.

#### Example A. Removal of Arsenic from Synthetic Solutions

Arsenic removal from synthetic solutions was conducted using different precipitating chemicals. Initial arsenic concentration in the solution was maintained at 100 ppb, and pH was adjusted to 6-8.5 using lime and/or sodium hydroxide. After the addition of reagent, the mixture was conditioned for 10 minutes. It was filtered through a previously prepared 2" thick filter bed made by DE. The DE filter bed was made by filtering 4 gms of DE conditioned in 500 cc of water in a 4" diameter filter crucible. A coarse filter paper was used to form the filter bed using a vacuum filter. The solution was filtered using a vacuum filtration system.

Results obtained with the direct addition of different precipitating agents are given in Table 1.

**Table 1. Arsenic Removal from Synthetic Arsenic Solution**

Reagent, Addition, gm	pH	Initial As, ppb	Final As, ppb	% Removed
.25 gm $\text{LaCl}_3$	8.5	100	26	74
.25 gm $\text{FeCl}_3$	8.18	100	11	89
.25 gm $\text{AlCl}_3$	8.69	100	12	88
.25 gm $\text{La}_2(\text{CO}_3)_2$	8.8	100	15	85
.25 gm $\text{La}(\text{NO}_3)_3$	7.81	100	57	43
.25 gm $\text{Fe}_2(\text{SO}_4)_2$	7.8	100	55	45
.25 gm $\text{MgCl}_2$	9.11	100	42	58
.25 gm $\text{BaCl}_2$	8.84	100	52	48

Results showed that arsenic can be removed by addition of chemical agents. Removal efficiencies are between 43% - 89%.

**Example B. Arsenic Removal with Precipitated Mixed Hydroxides Followed by DE-Precoat Filtration**

- Precipitated Ferric Hydroxide

0.25 gm  $\text{FeCl}_3$  was dissolved in 100 cc of water. Ferric hydroxide was precipitated at pH 7.53 using lime. Different amounts of wet hydroxides were added to a 500 cc synthetic solution of arsenic. After 10 minutes conditioning time, it was filtered using a DE pre-coat filter. Results are given in Table 2.

**Table 2. As Removal with Precipitated Ferric Hydroxide**

Amount Added, gm	pH	Initial As, ppb	Final As, ppb
1	8.24	100	6
.5	7.86	100	24
.25	8.11	100	35

As can be seen, 1 gm of precipitated ferric hydroxide can reduce the As level below 10 ppb. A low amount is not as effective as a high amount.

- Precipitated Lanthanum Hydroxide

Lanthanum hydroxide was prepared from lanthanum chloride and/or lanthanum nitrate by adding lime at pH 10.0. .5 grams of lanthanum salts were dissolved in 100 cc of water. Precipitate was collected after filtration. One gram of wet precipitate was added to 500 cc of arsenic containing solutions. Results are shown in Table 3.

**Table 3. Removal of Arsenic from Synthetic Solution using Lanthanum Hydroxide**

Amount Precipitated, gm	pH	Initial As, ppb	Final As, ppb
1	7.49	100	15
1	8.12	100	32

Results showed that lanthanum hydroxide is capable of removing arsenic from synthetic solution.

- Mixed Precipitated Hydroxides of Iron and Lanthanum for As Removal

Mixed hydroxides of iron and lanthanum were prepared by mixing  $\text{FeCl}_3$  and  $\text{LaCl}_3$  (prepared from lanthanum carbonate) by adding lime at pH ranges of 8-9. Mixed precipitate was prepared at three different weight ratios of Fe to La. Different amounts of precipitate were added to a synthetic solution containing 100 ppb of arsenic and mixed for 10 minutes. Results are shown in Table 4.

Schedule A: Fe:La Weight Ratio 1:1      Prepared by mixing 0.25 gm  $\text{FeCl}_3$  plus 0.25 gm  $\text{La}_2(\text{CO}_3)_3$  in HCl and then pH raised to 8.84 with lime

**Schedule B:** Fe:La Weight Ratio 2:1 Prepared by mixing 0.25 gm  $\text{FeCl}_3$  and 0.125 gm  $\text{La}_2(\text{CO}_3)_3$  in HCl and then pH raised to 8.2 with lime

**Schedule C:** Fe:La Weight Ratio 1:4 Prepared by mixing 0.25 gm  $\text{FeCl}_3$  and 0.625 gm  $\text{La}_2(\text{CO}_3)_3$  in HCl and then pH raised to 8.6 with lime

**Table 4. Effect of Mixed Hydroxides on As Removal from Synthetic Solution**

Schedule Type	Amount of Precipitate Added, gm	Initial As, ppb	Final As, ppb
A (1:1)	1	100	7
	.5	100	57
	.25	100	74
B (2:1)	0.5	100	25
	0.25	100	45
C (1:4)	0.5	100	29
	0.25	100	25

Mixed hydroxide-gels of iron and lanthanum are effective to remove arsenic. Different ratios of ferric and lanthanum can be mixed to remove different amounts of arsenic. At a ratio of 1:1, 1 gm of mixed precipitate can effectively decrease arsenic from 100 ppb to 7 ppb.

**Example C. Enhanced Coagulation of Arsenic from Fernley Drinking Water with Precipitate Hydroxide-gel Followed by DE Pre-coat Filtration**

In these tests, drinking water obtained from a well in Fernley, Nevada was tested. The direct addition of chemical coagulant for arsenic has several disadvantages. They are:

- (1) needs longer conditioning to precipitate and coagulate arsenic;
- (2) anions such as chlorides, sulfate or nitrates are released to drinking water which needs to be removed;
- (3) bonding of arsenate is not strong;
- (4) pH control is required to coagulate arsenate and arsenite ions;

(5) excessive reagent demand;

(6) size of a coagulant is small during direct addition; As a result, incomplete removal of arsenic may occur during separation.

In order to avoid the above mentioned problems and increase the arsenic removal efficiency, a novel precipitated hydroxide-gel coagulant process has been developed. This process is uniquely suitable for inexpensive pre-coat filtration using DE material. Results obtained with lanthanum hydroxides in combination with other hydroxides are given below in Tables 5-7.

- Tests with Pure Lanthanum Hydroxide

Five grams of lanthanum carbonate was dissolved in hydrochloric acid at pH 1.0. Lanthanum hydroxide was precipitated at pH 10.0 using lime. Precipitate was filtered. Total weight of hydroxide was 5 grams (on wet basis). 1.25 gms of weight of precipitate was added to Fernley drinking water. The pH was 8.70. After different conditioning times, it was filtered through a DE pre-coat filter. Results are given in Table 5.

**Table 5. Arsenic Removal from Fernley Drinking Water**

Time, min.	Initial As, ppb	Final As, ppb
5	68	6
10	68	2
240	68	Non-detectable

As can be seen, direct addition of precipitated lanthanum hydroxide is capable of reducing the arsenic level in Fernley drinking water to less than 10 ppb in 5 minutes. After 10 minutes it was 2 ppb.



- Test with Precipitated Ferric Hydroxide

0.25 gms of  $\text{FeCl}_3 \cdot 7\text{H}_2\text{O}$  was dissolved in 100 cc water. Ferric hydroxide was precipitated at pH 7.5 using lime. Total weight of precipitate was 2 grams on weight basis. One gram of wet precipitate was added to 500 cc of Fernley drinking water. The pH of the solution was 8.03. After the specified conditioning time, it was filtered using DE pre-coat filtration. Results are given in Table 6.

**Table 6. As Removal from Fernley Drinking Water with Ferric Hydroxide**

Time, min.	Initial As, ppb	Final As, ppb
5	68	15
10	68	6
240	68	5

As can be seen, precipitated ferric hydroxide is capable of removing arsenic from drinking water. After 10 minutes, the concentration of As was below 10 ppb.

- Tests with Precipitated Lanthanum Hydroxide plus Ferric Hydroxide

In another experiment, reduced amounts of ferric chloride and lanthanum chloride were used for precipitation. In this experiment, 0.25 gm  $\text{FeCl}_3 \cdot 7\text{H}_2\text{O}$  and 0.25 gm of  $\text{LaCl}_3$  (prepared from  $\text{LaCO}_3$ ) were mixed in 100 cc of water. The pH was increased to 8.80 using lime. The mixed precipitate was filtered. The total weight of precipitate was 5 grams. 2.5 grams of weight precipitate was added to the Fernley drinking water at a pH of 8.01. After conditioning for a specified time, the solution was filtered using DE pre-coat filtration. Results are given in Table 7.

**Table 7. Arsenic Removal with Mixed Precipitated Hydroxides**

Time, min.	Initial As, ppb	Final As, ppb
5	68	18
10	68	7
240	68	5

Precipitated mixed hydroxide-gels of iron and lanthanum can reduce the arsenic level below 10 ppb at a lower concentration.

- Effect of Mixed Hydroxide Dosage on Arsenic Removal

As described in Table 7, the mixed hydroxide precipitate was prepared by mixing an equal weight of  $\text{FeCl}_3 \cdot 7\text{H}_2\text{O}$  and  $\text{LaCl}_3$ . In another series of experiments, mixed hydroxides were prepared by using different iron-to-hydroxide ratios. Different amounts of mixed hydroxides were added to Fernley drinking water. After mixing for a specified time, it was filtered using a DE pre-coat filter. Results are given in Tables 8-10.

**Table 8. Tests with Ferric Hydroxide (prepared by precipitating 0.25 gm  $\text{FeCl}_3$  with lime at pH of 7.5); total precipitate = 2.0 grams (wet); conditioning time = 10 minutes**

Amount of Ferric Hydroxide Gram/500cc	Initial As, ppb	Final As, ppb
1	67	6
0.5	67	24
0.25	67	38

The above results showed that ferric hydroxide concentration should be 1 gm/liter (equivalent to .12 gm  $\text{FeCl}_3$ ). Below that concentration it is difficult to reduce As from Fernley water below 10 ppb.

- Effect of Direct Addition of Ferric Chloride and Ferric Sulphate

In another series of experiments, chemical grade ferric chloride and ferric sulfate were directly added to Fernley drinking water. The pH of the water was increased to 8.2 with lime and it was mixed for 30 minutes. After 30 minutes of mixing, it was filtered through the previously prepared DE-bed.

**Table 9. Tests with  $\text{FeCl}_3$  (alone) and  $\text{FeSO}_4$  direct addition; Fernley water 500cc**

Salt, gms	Initial As Concentration, ppb	Final As Concentration, ppb
$\text{FeCl}_3$ (.25 gm)	67	11 (5 min)
$\text{FeCl}_3$ (.25 gm)	67	<10 (10 min)
$\text{FeSO}_4$ (.25 gm)	67	21 (5 min)
$\text{FeSO}_4$ (.25 gm)	67	<10 (10 min)

These tests show that  $\text{FeCl}_3$  or  $\text{FeSO}_4$  direct addition can decrease As concentration below 10 ppb. However, a higher amount of ferric chloride is needed as compared to hydroxides. Further, longer mixing time and pH adjustment is required. The disadvantage of the direct addition is that the chloride and sulfate ions present in water have to be removed

**Table 10. Tests with Combined Ferric Hydroxide plus Lanthanum Hydroxide Prepared by mixing 0.25 gm  $\text{La}_2(\text{CO}_3)_3$  plus 0.25 gm  $\text{FeCl}_3$ ; Total hydroxide = 5 gms (wet basis)**

Amount of ppt, gm	Initial As Concentration, ppb	Final As Concentration, ppb
1	67	7
.5	67	57
.25	67-68	67-68

As can be seen, 1 gm of combined hydroxide-gel precipitate can decrease As concentration below 10 ppb. Lower concentration of precipitate is ineffective.

**Table 11. Tests with Combined Lanthanum Hydroxide and Ferric Hydroxide at Lower Concentration; (.125 gm  $\text{La}_2(\text{CO}_3)_3$  plus 0.25 gm  $\text{FeCl}_3$ ; total ppt = 1.6 gm)**

Amount of ppt, gm	Initial As Concentration, ppb	Final As Concentration, ppb
.5	67	29 (5 min)
.5	67	10 (10 min)
.25	67	25 (5 min)
.25	67	23 (10 min)

These results show that small additions of  $\text{La}(\text{OH})_3$  will decrease  $\text{FeCl}_3$  addition to achieve 10 ppb.

#### **Example D. Scale-up Test Using Mixed Hydroxides**

A series of experiments were conducted using five gallons of Fernley drinking water, in this case, hydroxide-gels prepared by mixing lanthanum chloride and ferric chloride in a ratio of 1:4. In one case, precipitation of hydroxides was conducted using chemical grade lime and in another case, chemical grade  $\text{MgO}$  was used.

Arsenic removal as a function of hydroxide-gel addition is given in Figure 2. As can be seen, hydroxide precipitate prepared using lime and  $\text{MgO}$  are effective in removing arsenic from water. However, hydroxide-gel prepared using lime is more effective than that of the precipitate prepared using  $\text{MgO}$ .

#### **Example E. DE-coated Hydroxides (La + Fe) Tests**

In these tests, lanthanum and iron hydroxides were precipitated at a ratio of 1:4 weight percent, respectively. Precipitation of hydroxides was conducted using lime at pH 9-10. Precipitates were filtered using the DE-pre coat filtration method. The DE-precoat filter bed was prepared by mixing 4 grams DE in 500 cc of water and filtering the mixture through a filter device. The thickness of the bed was around 1 inch thick. DE-coated hydroxide precipitate was used in the arsenic removal test. Results are given in Table 12.

**Table 12. Conditions: 500 cc Fernley Drinking Water; pH = 8.36**

Amount, gms	Initial As, ppb	Conditioning Time, min	Final As, ppb	% Removed
3 gms, DE-coated hydroxides (La + Fe)	93	5	8	91.3
3 gms DE-coated hydroxides (La + Fe)	93	10	6	93.5
3 gms DE-coated Hydroxide (Lanthanum Hydroxide only)	93	5	12	87.0
3 gms DE-coated Hydroxide (Lanthanum Hydroxide only)	93	10	10	89.2

These experiments showed that DE-coated lanthanum iron hydroxides as well as DE-coated lanthanum hydroxide are efficient in removing arsenic from drinking water.

**Example F. Tests with Chlorinated Drinking Water Using Different Hydroxides**

Chlorinated drinking water was collected from the Fernley Water Treatment Facility. Arsenic removal tests were conducted using different hydroxides prepared in the laboratory. Experimental results are given in Table 13. In this case hydroxide-gels were prepared from commercial grade lanthanum carbonate by mixing with ferric chloride and precipitated with lime.

Table 13. Conditions: 500 cc of Fernley water; pH = 6.7

Amount of hydroxide-gels added, gm	Initial As, ppb	Conditioning time, min.	Final As Concentration, ppb	% Removed
1 gm hydroxides (from lanthanum hydroxides)	80	5	5	93.7
1 gm (Iron + lanthanum hydroxides)	80	10	<5	~100
.25 gm aluminum hydroxide	80	5	11	86.2
.25 gm aluminum hydroxide	80	10	<5	~100
1 gm hydroxide (aluminum hydroxide + lanthanum hydroxide)	80	5	11	
1 gm hydroxide (aluminum hydroxide + lanthanum hydroxide)	80	10	<5	100
1 gm hydroxide ppt. (aluminum hydroxide + iron hydroxide)	80	5	10	
1 gm hydroxide ppt. (aluminum hydroxide)	80	10	<5	100

Tests conducted with different hydroxides (prepared from their respective salts) were effective in removing arsenic from drinking water using DE-precoat filters. Arsenic removal from chlorinated water is much easier as compared to non-chlorinated water.

#### **Example G. Evaluation of Different Pre-coat Filter Materials for As Removal**

In the following tests, hydroxide-gels of iron and lanthanum were used to coagulate arsenic from water. One gram of the hydroxide-gel sludge prepared by combining ferric chloride and lanthanum carbonate was added and mixed in 500 cc of Fernley water at a pH range of 8.3-8.5. Results are given in Table 14.

**Table 14. Effect of Different Pre-coat Filtering Materials in As Removal after Coagulation**

Type of Pre-coat Materials	Amount of Hydroxide / gm	Conditioning time, min.	Initial As, ppb	Final As, ppb
DE-bed	1	5	100	9
DE-bed	1	10	100	4
Cellulose-bed	1	5	100	29
Cellulose-bed	1	10	100	26
Perlite-bed	1	5	100	13
Perlite-bed	1	10	100	2

- DE - Eagle-Picher Diatomaceous Earth
- Cellulose - Eagle-Picher, PB-40M cellulose
- Perlite - Eagle-Picher, CP-1400 Perlite

DE was much more effective than either perlite or cellulose. Cellulose was not as effective as DE.

#### **Example H. Evaluation of DE-coated Hydroxide-gel Mixed at Different Ratios**

In another experiment, hydroxide-gels of lanthanum and ferric were filtered through a previously prepared DE bed. The DE containing hydroxide-gel was mixed with Fernley water for a different time. After mixing, it was filtered through a pre-coat DE filter bed. Results are given in Table 15.

**Table 15. DE Containing Hydroxide-gel for Arsenic Removal**

Initial As Concentration, ppb	Amount of Precipitate [DE+La(OH) <sub>3</sub> ] added to solution, gm	pH of Solution	As Concentration in Filtrate after 5 min. & 10 min., ppb
86	3	8.45	9, 8

Initial As Concentration, ppb	Amount of Precipitate [DE+La(OH) <sub>3</sub> +Fe(OH) <sub>3</sub> ] (La:Fe) (1:4) added to solution, gm	pH of Solution	As Concentration in Filtrate after 5 min. & 10 min., ppb
86	3	8.31	7, 6

Initial As Concentration, ppb	Amount of Precipitate [DE+La(OH) <sub>3</sub> +Fe(OH) <sub>3</sub> ] (La:Fe) (1:2) added to solution, gm	pH of Solution	As Concentration in Filtrate after 5 min. & 10 min., ppb
86	3	8.45	5, 4

Results given in Table 15 showed that DE-containing hydroxide-gels are powerful coagulants for removing arsenic from drinking water. It is seen that a DE-precoat filter is uniquely suitable for DE-containing hydroxide-gels.

All references cited herein are hereby incorporated by reference to the extent not inconsistent with the disclosure herewith. Although this description contains many specificities, these should not be construed as limiting the scope of the invention, but merely providing illustrations of some of the preferred embodiments of the invention. For example, metal salt hydroxide gels other than those specifically illustrated may be used. All numerical ranges given herein include all values and intermediate ranges. The invention is further described by the following exemplary claims.



## References

- Ahmann, D., Krumholz, L.R., Hemond, H.F., Lovley, D.R., and Morel, F.M.M., 1997, "Microbial Mobilization of Arsenic from Sediments of the Aberjona Watershed," *Environ. Sci. Technol.*, 31:2923-2930.
- Davis, S. and Misra M., "Transport Model for the Adsorption of Oxyanions of Selenium (IV) and Arsenic (V) from Water Onto Lanthanum and Alumina Oxides", *Journal of Colloid & Interface Science*, 188, 1997, p. 340-350.
- EPA, 2002, EPA Implements Standard of 10 ppb – <http://www.epa.gov/safewater/arsenic.html>
- Gupta, S.K. and Chen, K.Y., "Arsenic Removal by Adsorption," 50(3) *Journal of Water Pollution Control Federation*, 493, Mar. 1978.
- Harper, T.R. and Kingham, N.W. "Removal of Arsenic from Wastewater using Chemical Precipitation Methods," 64(3) *Water Environment Research* 200-203, 1992.
- Merrill, D.T., et al., "Field Evaluation of Arsenic and Selenium Removal by Iron Coprecipitation," 6(2) *Environmental Progress* 82-90, 1987.
- Misra, M. and Nayak, D., U.S. Patent No, 5,603,838.
- Misra, M., et al., U.S. Patent No. 6,197,201.
- Misra, M., Raichur, A.M. and Keltner, K., "Adsorption and Separation of Arsenic from Process Water Using LS<sup>TM</sup> (Lanthanum-Silica Compound)," *Proceedings of the Randol Gold Forum '97*, 1997, pp. 203-206.
- Misra, M. and Adutwum, K.O., "Adsorption of Oxyanions of Selenium Onto Lanthanum Oxide and Alumina," *Minor Elements 2000*, Published by SME, Feb. 2000, pp. 345-353.

Misra, M., Nanor, J., and Bucknam, C.H., "Enhanced Precipitation and Stabilization of Arsenic from Gold Cyanidation Process," Minor Elements 2000, Published by SME, Feb. 2000, pp. 141-148.

Nanor, J. and Misra, M., "Removal and Stabilization of Arsenic," Randol Gold Forum, 1999, pg. 191-196.

National Academy of Sciences, "Arsenic-Medical and Biological Effects of Environmental Pollutants," U.S. Government Printing Office, Washington, D.C., 1977.

National Research Council, Arsenic in Drinking Water, Washington D.C., National Academy Press, 1999.

Rawat, A. and Misra, M., "Adsorption of the Oxyanions of Arsenic onto Lanthanum Oxide," EPD Congress, The Minerals, Metals and Materials Society (TMS), Warrendale, PA, 1998, pp. 14-23.

Wasay, S.A., et al. "Removal of Arsenite and Arsenate Ions from Aqueous Solution by Basic Yttrium Carbonate," 30(5) Wat. Res. 1143-1148, 1996.

## CLAIMS

We claim:

1. A method of removing arsenic from arsenic-containing water comprising: contacting said water with a composition comprising a metal salt hydroxide-gel; and passing said composition through a filter, whereby arsenic-removed water is formed.
2. The method of claim 1, wherein said filter is a DE filter bed.
3. The method of claim 2, wherein said filter is a DE filter bed coated with a metal salt hydroxide-gel.
4. The method of claim 1, further comprising precipitating said metal salt hydroxide-gel prior to contacting said water with said composition.
5. A method of removing arsenic from arsenic-containing water comprising: coating DE with one or more metal salt hydroxide-gels to form DE pre-coated hydroxide-gels; and contacting said arsenic-containing water with said DE pre-coated hydroxide-gels.
6. The method of claims 1 or 5, wherein said metal salt hydroxide-gel is precipitated from a member of the group consisting of: lanthanum chloride, lanthanum nitrate, lanthanum carbonate, ferric chloride, ferric sulfate, magnesium chloride, magnesium nitrate, magnesium carbonate, aluminum chloride, aluminum nitrate, aluminum sulfate, and sodium aluminate.
7. The method of claim 6, wherein said composition comprises more than one different metal salts.
8. The method of claim 1, wherein said composition is contacted with said arsenic-containing water at a pH from about 2 to about 14.
9. The method of claim 1 or 5, wherein said arsenic-containing water contains arsenic at a concentration of about 10 ppb to 100 ppm.

10. The method of claim 9, wherein said arsenic-containing water contains one or more members selected from the group consisting of: arsenite, arsenate, arsenite and arsenate.

11. The method of claim 10, wherein said arsenic-containing water comprises one or more members of the group selected from: raw water, well water, drinking water, and process water.

12. The method of claim 11, wherein said composition is contacted with said arsenic-containing water for a time of between about 1 minute to about 6 minutes at a pH between about 3 and about 12.

13. The method of claim 1 or 5, wherein said metal salt hydroxide-gel comprises lanthanum and iron.

14. The method of claim 1 or 5, wherein said lanthanum and iron are added to said water at weight ratios of between about 1:1 and 1:10 of lanthanum:iron.

15. The method of claim 1 or 5, wherein said filter is selected from the group consisting of: diatameous earth (DE), cellulose, and perlite.

16. The method of claim 1 wherein said contacting step is performed using a member of the group consisting of: mechanical mixing, ultrasonic mixing, mixing in-line using an atomizer, mixing in-line using venturi and using metering pumps.

17. The method of claim 1 or 5, wherein said metal salt hydroxide-gel is lanthanum hydroxide.

18. The method of claim 1 or 5, wherein said metal salt hydroxide-gel is a rare earth hydroxide

19. The method of claim 1, further comprising separating the arsenic-removed water from said filter.

20. The method of claim 19, wherein said separating step is performed using DE-assisted settling or DE-assisted centrifuge.

21. The method of claim 19, wherein said separating step is performed using settling or flotation of hydroxide-gels.

22. The method of claim 2, wherein said filter is DE coated on a polyethylene filter screen.

2000-01-01 10:00:00

# ABSTRACT

A method of removing arsenic from water includes mixing precipitated hydroxide-gels prepared from lanthanum and ferric is provided. The arsenic present in water is adsorbed onto the hydroxide-gels which can effectively be filtered through a pre-coat diatomaceous earth (DE) filtration bed. The combination of DE mixed hydroxide-gels is also effective in removing arsenic from water.

503139-641002





Figure 1



**Figure 2: Arsenic Removal from Fernley Drinking Water**



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**